## NSN 5930-00-203-5594

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-203-5594

**Thread Class:** 

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

**Overall Length:** 

1.859 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.187 inches single actuator

**Overall Diameter:** 

1.344 inches

**Individual Section Quantity:** 

1

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

**End Application:** 

F-16 aircraft.

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

8 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

### **Switch Actuator Indexing Position Quantity:**

8 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

# NSN 5930-00-203-5594

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0