

View Online at <https://aerobasegroup.com/nsn/5930-00-203-5916>

Thread Class:

2b 1st mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

9.625 inches

Overall Height:

4.125 inches

Overall Width:

4.375 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches 2nd mounting facility

Individual Section Quantity:

10

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

3.812 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Round threaded hole shaft

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0