## NSN 5930-00-204-0471

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-204-0471

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 5.875 inches **Overall Height:** 1.875 inches **Overall Width:** 1.750 inches **Shaft Diameter:** 0.250 inches 2nd actuator **Shaft Length:** 0.531 inches 1st actuator **Overall Diameter:** 1.875 inches **Nonturn Device Radius:** 0.562 inches at 12: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Tab at 12: 00 o'clock **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 8 1st section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 8 2nd actuator **Shaft Type:** Round all actuators **Terminal Type:** 

Tab, solder lug

## NSN 5930-00-204-0471

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
Contact	Switching	ACLION.

Makes before breaks each section front

**Switch Actuator Positioning Increment:** 

20.0 degrees 2nd actuator

**Switch Actuator Stop Device Type:** 

Fixed stop all actuators

**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0