

View Online at <https://aerobasegroup.com/nsn/5930-00-204-7568>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

1.475 inches

Overall Height:

1.904 inches

Overall Width:

1.400 inches

Bushing Length:

0.468 inches

Body Length:

1.475 inches

Body Width:

1.400 inches

Body Height:

1.050 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.216 inches

Actuator Height:

Between 0.312 inches and 0.368 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained and left position momentary

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0