NSN 5930-00-204-8099

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-204-8099 |
|---|
| Hazardous Locations/environmental Protection: |
| Explosion proof |
| Overall Length: |
| 7.126 inches |
| Overall Height: |
| 2.813 inches |
| Overall Width: |
| 2.813 inches |
| Individual Section Quantity: |
| 4 |
| Knob Manufacturer Code: |
| 82121 |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.296 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.296 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 7 each section front |
| Features Provided: |
| Actuator knob and push to turn |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 125.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 8 single actuator |
| Terminal Type: |

_ . . .

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

NSN 5930-00-204-8099

Rotary Switch - Page 2 of 2



| Sty | le | De | sig | ına | ito | r | |
|-----|----|----|-----|-----|-----|---|--|
| | | | | | | | |

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0