

View Online at <https://aerobasegroup.com/nsn/5930-00-205-9806>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.281 inches single mounting facility

**Overall Length:**

Between 2.489 inches and 2.613 inches

**Overall Height:**

1.188 inches

**Overall Width:**

1.188 inches

**First Flat Length:**

0.218 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.656 inches single actuator

**Nonturn Device Radius:**

0.438 inches at 12: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**End Application:**

Guided missile, intercept

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

12 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts silver

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0