## NSN 5930-00-208-4108

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-208-4108

| Overall Length:   |
|---|
| 1.656 inches  |
| Overall Height:   |
| 3.188 inches  |
| Overall Width:  |
| 6.078 inches  |
| Body Height:  |
| 2.375 inches  |
| Capillary Tube Length:  |
| 24.000 inches   |
| Bulb Length:  |
| 15.375 inches   |
| Bulb Diameter:  |
| 0.188 inches  |
| Tempurature Sensing Element Type:   |
| Capillary tube-bulb   |
| Mounting Method:  |
| Surface   |
| Contact Action Stimulus:  |
| Increase  |
| Nonpile-up Contact Arrangement:   |
| 2 pole, single throw, normally closed, momentary action   |
| Terminal Type:  |
| Tab w/screw   |
| Contact Load Current Rating:  |
| 35.0 amperes resistive load second voltage  |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable   |
| Contact Adjustment Range:   |
| +60.00/+250.00 actuation point degrees fahrenheit and +60.00/+250.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type:  |
| External deactuation point knob with scale and external actuation point knob with scale                   |
| Contact Voltage Rating In Volts:  |
| 250.0 ac at sea level first voltage   |
| Media For Which Designed:   |
| Gas   |
| Style Designator:   |
| Rectangular   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5930-00-208-4108

Thermostatic Switch - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A048b0