

View Online at <https://aerobasegroup.com/nsn/5930-00-211-1896>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.500 inches

**Bushing Length:**

Between 0.485 inches and 0.515 inches

**Body Length:**

Between 0.984 inches and 1.016 inches

**Actuator Diameter:**

Between 0.485 inches and 0.515 inches

**Actuator Height:**

Between 0.495 inches and 0.525 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0