

View Online at <https://aerobasegroup.com/nsn/5930-00-213-6356>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.953 inches

Overall Height:

2.516 inches

Overall Width:

1.656 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

24.000 inches

Bulb Length:

11.875 inches

Bulb Diameter:

0.188 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Unthreaded hole

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

30.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+450.00 actuation point degrees fahrenheit and +90.00/+310.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0