

View Online at <https://aerobasegroup.com/nsn/5930-00-214-1309>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.438 inches 1st mounting facility

**Overall Length:**

6.406 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Individual Section Quantity:**

5

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

A

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing w/panel seal 1st mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 2nd mounting facility

**Thread Size:**

0.625 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A052b0