

View Online at <https://aerobasegroup.com/nsn/5930-00-214-1836>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.365 inches single mounting facility and 0.385 inches single mounting facility

**Overall Length:**

Between 4.150 inches and 4.210 inches

**First Flat Length:**

0.215 inches 1st actuator and 0.223 inches 1st actuator

**Flat Height:**

0.365 inches 1st actuator and 0.385 inches 1st actuator

**Shaft Diameter:**

0.248 inches 1st actuator and 0.252 inches 1st actuator

**Shaft Length:**

0.920 inches 2nd actuator

**Overall Diameter:**

1.036 inches

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 4th section front

**Throw Quantity:**

7 3rd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

3 4th section

**Switch Actuator Indexing Position Quantity:**

7 3rd actuator

**Shaft Type:**

Round, flatted w/through hole 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees 4th actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0