

View Online at <https://aerobasegroup.com/nsn/5930-00-215-2872>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and corrosion proof and oiltight

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.470 inches

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Length:

1.130 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.188 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Maximum Voltage Rating In Volts:

250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.25 ounces

Criticality Code Justification:

Zzzy

Switch Actuating Force:

2.75 ounces

Actuator Movement:

0.350 pretravel inches and 0.031 overtravel inches and 0.065 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo1235

Terminal Type And Quantity:

3 screw

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0