

View Online at <https://aerobasegroup.com/nsn/5930-00-215-2872>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof and corrosion proof and oiltight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

1.470 inches

**Unthreaded Mounting Hole Diameter:**

0.139 inches

**Actuator Length:**

1.130 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.188 inches

**Actuator Roller Diameter:**

0.370 inches

**Actuator Roller Width:**

0.150 inches

**Maximum Voltage Rating In Volts:**

250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.25 ounces

**Criticality Code Justification:**

Zzzy

**Switch Actuating Force:**

2.75 ounces

**Actuator Movement:**

0.350 pretravel inches and 0.031 overtravel inches and 0.065 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo1235

**Terminal Type And Quantity:**

3 screw

**Reference Number Differentiating Characteristics:**

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0