

View Online at <https://aerobasegroup.com/nsn/5930-00-215-4739>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.245 inches single mounting facility and 0.255 inches single mounting facility

**Overall Length:**

Between 1.306 inches and 1.330 inches

**Overall Height:**

1.531 inches

**Overall Width:**

1.406 inches

**First Flat Length:**

0.250 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.594 inches single actuator

**Nonturn Device Radius:**

0.521 inches at 3: 00 o'clock and 0.541 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, v flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

58189-810000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0