NSN 5930-00-215-4834

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-215-4834

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Overall Length:

3.562 inches

First Flat Length:

0.437 inches single actuator

Flat Height:

0.234 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.781 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

7 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks 3rd section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-00-215-4834

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0