

View Online at <https://aerobasegroup.com/nsn/5930-00-219-5734>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

12.000 inches

**Overall Height:**

2.813 inches

**Overall Width:**

2.813 inches

**Individual Section Quantity:**

21

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section front

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Special Features:**

Item must comply with rqmt of desc production standard no. L01263

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0