NSN 5930-00-219-5734

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-219-5734

Explosion proof
Overall Length:
12.000 inches
Overall Height:
2.813 inches
Overall Width:
2.813 inches
Individual Section Quantity:
21
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
8 each section front
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Criticality Code Justification:
Feat
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator

NSN 5930-00-219-5734

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Special Features:

Item must comply with rqmt of desc production standard no. L01263

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0