

View Online at <https://aerobasegroup.com/nsn/5930-00-219-6877>

Thread Length:

0.234 inches single mounting facility and 0.266 inches single mounting facility

Width Between Flats:

0.184 inches single actuator and 0.188 inches single actuator

Overall Length:

Between 2.434 inches and 2.496 inches

First Flat Length:

0.314 inches single actuator and 0.336 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.594 inches single actuator and 0.656 inches single actuator

Overall Diameter:

Between 2.490 inches and 2.510 inches

Nonturn Device Radius:

0.526 inches at 9: 00 o'clock and 0.536 inches at 9: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 9: 00 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 3rd section front

Throw Quantity:

5 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at altitude

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

20 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

18.0 degrees single actuator

Style Designator:

Circular wafer, bushing mount

Test Data Document:

80063-sm-c-134943 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0