

View Online at <https://aerobasegroup.com/nsn/5930-00-219-8580>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

1.520 inches

Bushing Length:

1.000 inches

Body Length:

1.560 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.395 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.045 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0