## NSN 5930-00-219-8580

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-219-8580

| Body Style:  |
|--|
| Bushing mounted  |
| Hazardous Locations/environmental Protection:  |
| Weatherproof   |
| Body Diameter:   |
| 1.520 inches   |
| Bushing Length:  |
| 1.000 inches   |
| Body Length:   |
| 1.560 inches   |
| Actuator Style:  |
| Round  |
| Actuator Diameter:   |
| 0.250 inches   |
| Actuator Height:   |
| 0.375 inches   |
| Actuator Free Position Height:   |
| 0.395 inches   |
| Maximum Voltage Rating In Volts:   |
| 28.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing   |
| Thread Size:   |
| 0.625 inches   |
| Nonpile-up Contact Arrangement:  |
| 2 two circuit, double break/double make, one position momentary single switch unit       |
| Switch Release Force:  |
| 64.0 ounces  |
| Switch Actuating Force:  |
| 192.0 ounces   |
| Actuator Movement:   |
| Between 0.070 pretravel inches and 0.250 overtravel inches and 0.045 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc    |
| Thread Series Designator:  |
| Unef   |
| Terminal Type And Quantity:  |
| 8 wire lead  |
| Shelf Life:  |
| N/a  |

## NSN 5930-00-219-8580

Sensitive Switch - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A053a0