

View Online at <https://aerobasegroup.com/nsn/5930-00-220-6469>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant and vibration resistant

Overall Length:

0.683 inches

Overall Height:

1.607 inches

Overall Width:

0.511 inches

Bushing Length:

0.312 inches

Body Length:

0.683 inches

Body Width:

0.511 inches

Body Height:

0.550 inches

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

0.650 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

End Application:

C-130f hercules, e-6 tacamo aircraft, oliver perry class ffg.

Mounting Surface To Terminal End Distance:

0.645 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0