# NSN 5930-00-220-6687

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-220-6687

#### **Hazardous Locations/environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Overall Length:** 

3.760 inches

**Overall Height:** 

1.695 inches

**Overall Width:** 

1.200 inches

#### **Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:** 

6

#### **Longest Horizontal Distance Between Mounting Centers:**

3.590 inches single mounting facility

#### **Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

#### **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

# **Actuator Type:**

Thumbwheel all actuators

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Mounting Facility Pattern:**

Four position rectangular single mounting facility

# **Switch Actuator Indexing Position Quantity:**

10 all actuators

# **Terminal Type:**

Tab, solder lug

#### **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

# Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

# **Contact Arrangement Truth Table:**

Bcd with complement, 2 pole - 10 positions each section

#### Color:

Black each body

# **Precious Material And Location:**

Terminal surfaces gold

# **Precious Material:**

Gold

### **Style Designator:**

Rectangular inline indicating

# NSN 5930-00-220-6687

Code Indicating Wheel Switch - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0