NSN 5930-00-221-8354

Pressure Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-221-8354

2b single pressure connection **Inside Diameter:** 0.250 inches single connection **Overall Length:** 2.875 inches **Overall Height: 3.187** inches **Overall Width: 3.688** inches **Body Length:** 2.312 inches **Body Height:** 2.312 inches **Pressure Switch Type:** Gage **Mounting Method: Terminal** Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Thread Size:** 0.250 inches single pressure connection **Nonpile-up Contact Arrangement:** 2 pole, single throw, normally closed, momentary action **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 2.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point adjustable, preset and actuation point adjustable, preset **Contact Adjustment Range:** +10.00/+100.00 actuation point pounds per square inch and +27.00/+50.00 deactuation point pounds per square inch **Contact Adjustment Type:** External deactuation point screw and external actuation point screw **Contact Stimulus Rating:** 80.00 actuation point pounds per square inch and 100.00 actuation point pounds per square inch and 32.00 differential point pounds per square inch and 100.00 differential point pounds per square inch

Pressure Connector Type:

Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage

Plain, threaded internal single connection

NSN 5930-00-221-8354

Pressure Switch - Page 2 of 2



Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0