

View Online at <https://aerobasegroup.com/nsn/5930-00-222-6177>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

3.000 inches

**Overall Height:**

Between 5.000 inches and 6.250 inches

**Overall Width:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Distance Between Mounting Facility Centers:**

2.062 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

650.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.00/+250.00 actuation point pounds per square inch and +0.00/+250.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Pressure Connector Type:**

Swivel nut, gasket seal, threaded internal single connection

**Special Features:**

Open construction

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0