

View Online at <https://aerobasegroup.com/nsn/5930-00-222-6180>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

8.813 inches

Overall Height:

4.125 inches

First Flat Length:

0.750 inches single actuator

Flat Height:

0.250 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.125 inches single actuator

Individual Section Quantity:

16

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

2.281 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

1 each section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Special Features:

Item must comply with requirements of desc production standard no. L01221; for navy nuclear propulsion plant products only

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0