NSN 5930-00-224-2745

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-224-2745

| Thread Class. | | | | | | |
|--|--|--|--|--|--|--|
| Thread Class: | | | | | | |
| 2a | | | | | | |
| Body Style: | | | | | | |
| Bushing mount | | | | | | |
| Overall Length: | | | | | | |
| 0.094 inches | | | | | | |
| Overall Width: | | | | | | |
| 0.688 inches | | | | | | |
| Bushing Length: | | | | | | |
| 0.469 inches | | | | | | |
| Body Length: | | | | | | |
| 1.094 inches | | | | | | |
| Body Width: | | | | | | |
| 0.688 inches | | | | | | |
| Body Height: | | | | | | |
| 0.672 inches | | | | | | |
| Actuator Style: | | | | | | |
| Round | | | | | | |
| Actuator Height: | | | | | | |
| 0.500 inches | | | | | | |
| Actuator Position-action Relationship: | | | | | | |
| Up position maintained and down position maintained | | | | | | |
| Maximum Voltage Rating In Volts: | | | | | | |
| 250.0 ac and 250.0 dc | | | | | | |
| Inclosure Type: | | | | | | |
| Fully enclosed | | | | | | |
| Mounting Method: | | | | | | |
| Threaded bushing | | | | | | |
| Thready Qty Per Inch (tpi): | | | | | | |
| 32 | | | | | | |
| Thread Size: | | | | | | |
| 0.469 inches | | | | | | |
| Nonpile-up Contact Arrangement: | | | | | | |
| 1 pole, single throw, both positions maintained single switch unit | | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | | |
| 3.000 amperes resistive dc and 3.000 amperes resistive ac | | | | | | |
| Thread Series Designator: | | | | | | |
| Uns | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 tab, solder lug | | | | | | |
| Shelf Life: | | | | | | |
| | | | | | | |

N/a

NSN 5930-00-224-2745 Toggle Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

Demilitarization:

No

Fiig:

A053a0