NSN 5930-00-224-3753

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-224-3753 **Body Style:** Panel mount **Body Length:** 1.200 inches **Body Width:** 0.960 inches **Body Height:** 2.828 inches **Case Material:** Metal **Actuator Length:** 1.040 inches **Actuator Style:** Rectangular **Actuator Height:** 0.140 inches **Actuator Width:** 0.625 inches **Actuator Color:** White single actuator and green single actuator and natural single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 tab, solder lug and 6 turret **Specification Data:** 81349-mil-s-22885/9 government specification Shelf Life: N/a

Unit Of Measure:

Demilitarization:

NSN 5930-00-224-3753

Push Switch - Page 2 of 2



Fiig:

A053a0