

View Online at <https://aerobasegroup.com/nsn/5930-00-224-5096>

Thread Class:

2a

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

2.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.807 inches and 1.817 inches

Overall Height:

2.001 inches

Overall Width:

0.766 inches

Body Length:

2.125 inches

Body Width:

0.766 inches

Body Height:

1.062 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 0.859 inches and 0.891 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

440.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 10.000 amperes inductive dc and 18.000 amperes motor dc and 4.200 amperes resistive ac and 2.000 amperes inductive ac and 2.000 amperes motor ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0