## NSN 5930-00-224-5096

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-224-5096 **Thread Class:** 2a **Body Style:** Hole mount **Hazardous Locations/environmental Protection:** Submersible **Overall Length:** 2.130 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.807 inches and 1.817 inches **Overall Height:** 2.001 inches **Overall Width:** 0.766 inches **Body Length:** 2.125 inches **Body Width:** 0.766 inches **Body Height:** 1.062 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.235 inches and 0.245 inches **Actuator Height:** Between 0.859 inches and 0.891 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Maximum Voltage Rating In Volts:** 440.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.138 inches

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 10.000 amperes inductive dc and 18.000 amperes motor dc and 4.200 amperes resistive ac and 2.000 amperes inductive ac and 2.000 amperes motor ac

## **NSN 5930-00-224-5096** Toggle Switch - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0