

View Online at <https://aerobasegroup.com/nsn/5930-00-224-5382>

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

2.600 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.500 inches

Overall Diameter:

0.680 inches

Pressure Switch Type:

Absolute

Width Across Flats:

0.680 inches

Operating Temperature Rating:

Between 0.0 degrees celsius and 60.0 degrees celsius

Mounting Method:

Line

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

100.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

21.90 actuation point pounds per square inch absolute and 19.80 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0