NSN 5930-00-224-5551

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

3 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-224-5551

| Center To Center Distance Between Mounting Facilities Parallel To Length: | | |
|--|--|--|
| 1.000 inches | | |
| Overall Width: | | |
| 0.281 inches | | |
| Body Length: | | |
| 1.203 inches | | |
| Body Width: | | |
| 0.281 inches | | |
| Body Height: | | |
| 0.828 inches | | |
| Unthreaded Mounting Hole Diameter: | | |
| 0.094 inches | | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | | |
| 0.625 inches | | |
| Actuator Length: | | |
| 1.438 inches | | |
| Actuator Style: | | |
| Roller arm | | |
| Actuator Free Position Height: | | |
| 1.031 inches | | |
| Actuator Roller Diameter: | | |
| 0.250 inches | | |
| Maximum Voltage Rating In Volts: | | |
| 250.0 ac | | |
| Inclosure Type: | | |
| Fully enclosed | | |
| Mounting Method: | | |
| Unthreaded hole | | |
| Nonpile-up Contact Arrangement: | | |
| 1 pole, double throw, one position momentary single switch unit | | |
| Switch Release Force: | | |
| 0.5 ounces | | |
| Switch Actuating Force: | | |
| 2.0 ounces | | |
| Actuator Movement: | | |
| Between 0.156 pretravel inches and 0.062 overtravel inches and 0.060 differential inches | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | |
| 10.000 amperes resistive ac | | |
| Terminal Type And Quantity: | | |

NSN 5930-00-224-5551

Sensitive Switch - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0