NSN 5930-00-224-6162

Rotary Switch - Page 1 of 1

60.0 degrees single actuator

Contact Load Current Rating:

Style Designator:Tap, circuit selector

Unit Of Measure:

Demilitarization:

Shelf Life:

N/a

No Fiig: A052b0



View Online at https://aerobasegroup.com/nsn/5930-00-224-6162 **Overall Length:** 9.752 inches **Individual Section Quantity:** 12 **Longest Horizontal Distance Between Mounting Centers:** 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.180 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 24.0 lowest dc voltage rating at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility **Switch Actuator Indexing Position Quantity:** 6 single actuator **Switch Actuator Positioning Increment:**

6.0 amperes resistive load lowest dc voltage rating at sea level and 4.0 amperes inductive load lowest dc voltage rating at sea level