

View Online at <https://aerobasegroup.com/nsn/5930-00-224-7218>

Thread Length:

0.760 inches single threaded bushing

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.750 inches

Body Diameter:

0.610 inches

Body Length:

1.010 inches

Temperature Sensing Element Type:

Internal sensor

Width Across Flats:

Between 0.875 inches and 0.940 inches

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

6.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

285.00 actuation point degrees fahrenheit and 280.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/flange

Test Data Document:

81349-mil-s-12285 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Nptf single threaded bushing

Specification Data:

81349-mil-s-12285/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0