NSN 5930-00-225-0333

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-225-0333			
Thread Class:			
2b single mounting facility			
Hazardous Locations/environmental Protection:			
Dustproof			
Overall Length:			
9.469 inches			
Overall Height:			
4.125 inches			
Overall Width:			
4.125 inches			
Shaft Diameter:			
0.375 inches single actuator			
Shaft Length:			
1.250 inches single actuator			
Individual Section Quantity:			
5			
Switch Contact Basic Design:			
Nonpile-up nonsymmetrical			
Mounting Facility Circle Radius:			
1.906 inches single mounting facility			
Mounting Method:			
Bracket single mounting facility and threaded hole single mounting facility			
Features Provided:			
Actuator knob			
Thready Qty Per Inch (tpi):			
20 single mounting facility			
Thread Size:			
0.250 inches single mounting facility			
Contact Voltage Rating In Volts:			
500.0 highest ac voltage rating at sea level			
Mounting Facility Pattern:			
Four position circular single mounting facility			
Switch Actuator Indexing Position Quantity:			
4 single actuator			
Shaft Type:			
Round, hollowed single actuator			
Terminal Type:			
Screw			
Contact Switching Action:			
Breaks before makes each section front			

Switch Actuator Positioning Increment: 90.0 degrees single actuator

NSN 5930-00-225-0333

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guileiii	naumu.

10.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0