NSN 5930-00-225-0427

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-225-0427 **Thread Class:** 2a single mounting facility Thread Length: 0.469 inches single mounting facility **Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 5.938 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.438 inches single actuator **Overall Diameter:** 2.000 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number:** An-3220-3 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 8 each section front **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Round single actuator **Terminal Type:**

Screw

NSN 5930-00-225-0427

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0