

View Online at <https://aerobasegroup.com/nsn/5930-00-225-2392>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

10.750 inches

**Overall Height:**

2.125 inches

**Body Diameter:**

5.750 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Distance Between Mounting Facility Centers:**

2.000 inches

**Capillary Tube Length:**

144.0 inches

**Bulb Length:**

3.000 inches

**Bulb Diameter:**

0.688 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

120.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case and tubing end seal connection

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.00/+75.00 actuation point degrees fahrenheit and +0.00/+75.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point knob and external deactuation point knob

**Contact Voltage Rating In Volts:**

230.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0