NSN 5930-00-225-2392

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-225-2392

Userandaria La sotiana (anciente en tel Destastiano
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
10.750 inches
Overall Height:
2.125 inches
Body Diameter:
5.750 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Mounting Facility Centers:
2.000 inches
Capillary Tube Length:
144.0 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.688 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
120.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case and tubing end seal connection
Contact Action Stimulus:
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+0.00/+75.00 actuation point degrees fahrenheit and +0.00/+75.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

External actuation point knob and external deactuation point knob

NSN 5930-00-225-2392

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:

230.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0