

View Online at <https://aerobasegroup.com/nsn/5930-00-225-6640>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.516 inches

Outside Diameter:

0.500 inches single connection

Overall Width:

3.600 inches

Body Diameter:

3.500 inches

Body Length:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.218 inches

Distance Between Mounting Facility Centers:

2.875 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

700.00 actuation point pounds per square inch and 500.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0