## NSN 5930-00-225-8988

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-225-8988

**Thread Class:** 2b 1st mounting facility Thread Length: 0.438 inches 2nd mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 14.657 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 2.032 inches single actuator **Individual Section Quantity:** 27 **Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number: Longest Horizontal Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 3 each section rear **Mounting Facility Circle Radius:** 0.906 inches 2nd mounting facility **Mounting Method:** Threaded stud 2nd mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 1st mounting facility **Thread Size:** 0.190 inches 2nd mounting facility

125.0 ac at sea level

**Contact Voltage Rating In Volts:** 

## NSN 5930-00-225-8988

Rotary Switch - Page 2 of 2



## **Mounting Facility Pattern:** Four position rectangular 1st mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unf 2nd mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A052b0