

View Online at <https://aerobasegroup.com/nsn/5930-00-225-9888>

**Overall Length:**

5.750 inches

**Overall Height:**

10.938 inches

**Overall Width:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.062 inches

**Longest Vertical Distance Between Mounting Centers:**

4.250 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+500.00/+5000.00 actuation point pounds per square inch gage and +350.00/+4610.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0