NSN 5930-00-226-3322



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-226-3322 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.875 inches **Body Length:** 2.250 inches **Body Width:** 1.500 inches **Body Height:** 1.875 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.000 inches **Actuator Style:** Round **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.750 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Maximum Voltage Rating In Volts:** 50.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 4c 2nd position **Thread Size:** 0.112 inches **Contact Load Current Rating At Maximum Rated Voltage:** 400.000 milliamperes resistive dc **Thread Series Designator:**

Unc

Terminal Type And Quantity:

1 connector, receptacle

NSN 5930-00-226-3322

Lever Switch - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0