NSN 5930-00-226-5922



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-226-5922 **Body Style:** Panel mount **Overall Length:** 1.000 inches **Overall Height:** 2.200 inches **Overall Width:** 0.750 inches **Body Length:** Between 0.895 inches and 0.915 inches **Body Width:** Between 0.740 inches and 0.760 inches **Case Material:** Metal **Actuator Length:** Between 0.420 inches and 0.440 inches **Actuator Style:** Rectangular **Actuator Height:** 0.188 inches **Actuator Width:** Between 0.670 inches and 0.690 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc **Special Features:** 3 lamp terminals **Test Data Document:** 13499-266-6799-940 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 15 tab, solder lug

N/a

Shelf Life:

Unit Of Measure:

NSN 5930-00-226-5922

Push Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0