

View Online at <https://aerobasegroup.com/nsn/5930-00-226-6429>

**Thread Class:**

2b

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.812 inches

**Overall Height:**

2.563 inches

**Overall Width:**

0.969 inches

**Body Length:**

2.250 inches

**Body Width:**

0.969 inches

**Body Height:**

1.625 inches

**Actuator Style:**

Round

**Actuator Height:**

0.750 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

24.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc

**Precious Material And Location:**

Connector contacts silver

**Test Data Document:**

81349-mil-s-13735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 connector, receptacle

**Specification Data:**

96906-ms39061 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0