# NSN 5930-00-226-6542

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-226-6542

## **Body Style:**

Hole mounted

### **Overall Length:**

0.500 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

# **Overall Width:**

0.200 inches

#### **Body Length:**

0.500 inches

#### **Body Width:**

0.200 inches

### **Body Height:**

0.350 inches

### **Unthreaded Mounting Hole Diameter:**

# 0.087 inches

**Actuator Style:** 

Round

## Actuator Diameter:

Between 0.043 inches and 0.053 inches

## Actuator Height:

Between 0.020 inches and 0.030 inches

# Actuator Free Position Height:

0.0035 inches

## Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

## **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

#### Switch Release Force:

1.0 ounces

### Switch Actuating Force:

5.0 ounces

## **Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes resistive ac

# Terminal Type And Quantity:

3 solder stud

# NSN 5930-00-226-6542

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

