

View Online at <https://aerobasegroup.com/nsn/5930-00-227-7109>

**Inside Diameter:**

0.250 inches all connections

**Overall Length:**

4.500 inches

**Overall Width:**

5.000 inches

**Body Diameter:**

3.125 inches

**Body Length:**

2.780 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Mounting Facility Centers:**

2.813 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

40.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

7.5 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+0.40/+19.60 actuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point dial

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0