

View Online at <https://aerobasegroup.com/nsn/5930-00-227-7109>

Inside Diameter:

0.250 inches all connections

Overall Length:

4.500 inches

Overall Width:

5.000 inches

Body Diameter:

3.125 inches

Body Length:

2.780 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.813 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

7.5 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.40/+19.60 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point dial

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0