

View Online at <https://aerobasegroup.com/nsn/5930-00-227-7345>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.547 inches

Overall Height:

3.156 inches

Overall Width:

1.563 inches

Capillary Tube Length:

72.000 inches

Bulb Length:

5.625 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.562 inches

Longest Vertical Distance Between Mounting Centers:

2.938 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between 20.0 degrees fahrenheit and 90.0 degrees fahrenheit

Mounting Method:

Base

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

8.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+20.00/+90.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

40.00 actuation point degrees fahrenheit and 1.75 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Frequency In Hertz:

400.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0