

View Online at <https://aerobasegroup.com/nsn/5930-00-229-7930>

Thread Class:

2a single mounting facility

Thread Length:

0.302 inches single mounting facility and 0.322 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 2.287 inches and 2.363 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.124 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.657 inches single actuator and 0.717 inches single actuator

Overall Diameter:

Between 0.672 inches and 0.702 inches

Nonturn Device Radius:

0.245 inches at 3:00 o'clock and 0.275 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 lowest dc voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+8.000/+16.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0