NSN 5930-00-230-2562

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-230-2562
Body Style:
Bushing/hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Bushing Length:
0.500 inches
Body Length:
1.937 inches
Body Width:
0.687 inches
Body Height:
0.990 inches
Actuator Style:
Round
Actuator Diameter:
0.328 inches
Actuator Height:
0.339 inches
Actuator Free Position Height:
1.500 inches
Maximum Voltage Rating In Volts:
250.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 10.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.219 overtravel inches and 0.003 differential inches

Thread Series Designator:

Uns

NSN 5930-00-230-2562

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 screw
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0