NSN 5930-00-230-2574

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-230-2574

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.937 inches
Body Width:
0.687 inches
Body Height:
1.312 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
2.406 inches
Actuator Style:
Leaf
Actuator Width:
0.219 inches
Actuator Free Position Height:
0.935 inches
Maximum Voltage Rating In Volts:
250.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
1 pole, double throw, one position momentary single switch unit
1 pole, double throw, one position momentary single switch unit Switch Release Force:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw Shelf Life:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw Shelf Life: N/a
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw Shelf Life: N/a
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure:
1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.031 overtravel inches and 0.050 differential inches Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure: Demilitarization: